



FLOOR PLAN
 SCALE 1/8" = 1'-0"

LICENSED ARCHITECTS
 AP 11460
 JAMES T. GLANCEY
 STATE OF IDAHO
 3/12/09

KEY NOTES

- 1 REMOVE EXISTING DOOR SAVE FOR REUSE.
- 2 INFILL OPENING w/ 2x6 WD STUDS @ 16" O.C. w/ 5/8" GYP. BD. INTERIOR. EXTERIOR TO MATCH EXISTING, PROVIDE R19 INSULATION
- 3 REMOVE EXISTING WINDOW.
- 4 INSTALL SALVAGED DOOR.
- 5 1/4" TEMPERED GLASS SIDELIGHTS TO MATCH DOOR SET IN WOOD FRAME TO MATCH DOOR.
- 6 DEMO WALLS. PATCH AND MATCH CARPET AS NEEDED
- 7 LINE UP NEW WALL w/ EXISTING
- 8 NEW 12'-0" +/- NONBEARING PARTITION w/ 2x4 WD. STUDS @ 16" O.C. w/ 1 LAYER 5/8" GYP. BD. EACH SIDE. MATCH EXISTING.

HARDWARE SCHEDULE	
HARDWARE GROUP #1	HARDWARE GROUP #2
DOORS: D1 1 SET HINGES - EXISTING 1 EA CYLINDER LOCK - ONE SIDE - KEYED ONLY 1 EA PULL w/ LEVER 1 EA RIM EXIT DEVICE 1 EA. DOOR CLOSER w/ OVERHEAD STOP 1 EA. THRESHOLD - LESS THAN 1/2"	DOOR: D2 3 EA. 4 1/2" BUTT HINGES 1 EA. PUSH / PULL 1 EA. THRESHOLD - LESS THAN 1/2" 1 EA. DOOR CLOSER

DOOR SCHEDULE						
DOOR #	SIZE	CONSTRUCTION FRAME / DOOR		RATING	HARDWARE GROUP	NOTES
D1	E 3'-0" x 8'-0"	EXISTING		NONE	1	REUSE EXISTING DOOR
D2	3'-0" x 8'-0"	WOOD / GLASS		NONE	2	TEMPERED GLAZING