



TYPICAL CURBED STREET SECTION

N.T.S.

TABLE A - DIMENSIONS FOR STREET SECTIONS

	DESCRIPTION	COLLECTOR STREET	BUSINESS ZONE	INDUSTRIAL**
A	RECOMMENDED RIGHT-OF-WAY	80'	100'	80'
B	DISTANCE FACE-FACE OF CURB	44'	60' - 80'	44'
C	SIDEWALK WIDTH	5'	6'-10'	5'
D	CURB & GUTTER	TYPE 1	TYPE 1	TYPE 2
E	HOT PLANT MIX PAVEMENT	0.25'	0.25'	0.25'
F	3/4" MINUS AGGREGATE BASE	0.33'	0.33'	0.33'
G	2" MINUS AGGREGATE SUB-BASE	0.66'	0.66'	0.66'
H	ADDITIONAL BASE (as needed)	VARIES	VARIES	VARIES

**NOTE : Existing 60' ROW in Industrial zones shall be improved in conformance with the 80' ROW Standards.

NOTES

1. Tolerance for crown slope shall be 0.5%±.

REVISIONS

**2006 CITY OF HAILEY
IMPROVEMENT STANDARD
DRAWINGS**

CURBED STREET SECTION

801

DWG. NO.